



Rocker Guard

Part No. J003T

Fits: Jeep Wrangler YJ, TJ	1987-2006
----------------------------	-----------

PARTS LIST:			
Qty	Part Description	Qty	Part Description
1	Side Guard Set (Left and Right)	16	3/8" x 1" Self Tapping Bolts

TOLL FREE SUPPORT: 866 638 4870	Install Time : 30 – 60 Minutes (Professional Installation) Install Note : DRILLING REQUIRED
---------------------------------	--

REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT

READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION

INSTALLATION PROCEDURE

Step One: Locate hardware and check contents with the hardware listed below.

Step Two: Position the Guard up to the frame. Maintain a 1/2" minimum between the bottom of vehicle and the top of the Guard. Move the Guard from front to back till is parallel to the side of the frame. Also make sure it is parallel to the bottom of the vehicle. Assistance is recommended while positioning Guard up to frame.

Step Three: Mark the side of the frame through the mounting holes located in the Guard Bracket. Then place Guard aside. Center punch the frame where you marked and drill a 5/16" hole in the frame. **CAUTION:** Before drilling be sure to check the backside of the frame for possible hazards or obstructions.

Step Four: Position Guard back to the frame and line up holes in the mounting brackets with just drilled holes in the frame. Secure the Guard to the frame with the included 3/8" x 1" Self Tapping bolts. Fully tighten all hardware at this time. Be sure to use all hardware supplied and tighten all bolts.

Step Five: Repeat steps two through four for the opposite side.

Side Rocker Guard Shown



Side Armor Guard Shown



Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Sidebar.

For gloss black finishes: Mild soap may be used to clean the Product.

Keystone Automotive Operations Inc. (KAO) warrants this product to be free of defects in material and workmanship at the time of purchase by the original retail consumer. KAO disclaims any other warranties, express or implied, including the warranty of fitness for a particular purpose or an intended use. If the product is found to be defective, KAO may replace or repair the product at our option, when the product is returned prepaid, with proof of purchase. Alteration to, improper installation, or misuse of this product voids the warranty. KAO's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for any incidental or consequential loss or damage.