

Part No. J006

Fits: Jeep Wrangler JK 2DR 2007-2012

TOLL FREE SUPPORT: 866 638 4870

Install Time : 30 – 60 Minutes

(Professional Installation)

Install Note

REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT

READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION

INSTALLATION PROCEDURE

1. Locate the four (4) body mounts at the rear of the front wheel well, and in front of the rear wheel well (two mounts per side). Start by removing the 18mm center body mount bushing bolts on each body mount (some force may be required).



2. Once the center bolts are removed, remove the remaining two (2)16mm nuts located on either side of the bolt. Do this for each of the four (4) body mounts.


Page 1 of 3 Rev 031412



3. Supporting the RRC Side Armor from underneath, lift the Armor into place and slide it between the large washer and the body mount, taking care to align the holes in the Armor mount with the two body mount studs. Apply several drops of thread locker to the studs. Thread the two nuts onto the studs loosely. Repeat for each body mount location.




4. Once all the nuts have been loosely threaded and the Armor is attached to the vehicle, begin tightening the nuts to 40-ft/lbs. Repeat for each mounting location.



5. Once all the nuts have been tightened, tighten the center bolt of the body mount to 80-ft/lbs. Repeat for

Page 2 of 3 Rev 031412

each mounting location.



6. Installation is now complete.



Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Sidebar.

For gloss black finishes: Mild soap may be used to clean the Product.

Keystone Automotive Operations Inc. (KAO) warrants this product to be free of defects in material and workmanship at the time of purchase by the original retail consumer. KAO disclaims any other warranties, express or implied, including the warranty of fitness for a particular purpose or an intended use. If the product is found to be defective, KAO may replace or repair the product at our option, when the product is returned prepaid, with proof of purchase. Alteration to, improper installation, or misuse of this product voids the warranty. KAO's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for any incidental or consequential loss or damage.

Page 3 of 3 Rev 031412