

**Trailblazer Rocker Guard****PART NUMBER**

42-4005

**REQUIRED TOOLS**

- Ratchet
- Torque Wrench
- Drill, 5/16" Drill Bit

**PARTS**

QTY	PRODUCT
1	Rocker Guard Set (Left and Right)
16	3/8" x 1" Self Tapping Bolts

**WARRANTY**

3 YEARS

Side Rocker Guard Shown



Drilling and Mounting Location

**INSTRUCTIONS:**

1. Locate hardware and check contents with the hardware listed.
2. Position the Rocker Guard up to the frame. Maintain a 1/2" minimum between the bottom of vehicle and the top of the Rocker Guard. Move the Guard from front to back till is parallel to the side of the frame. Also make sure it is parallel to the bottom of the vehicle. Assistance is recommended while positioning Guard up to frame.

3. Mark the side of the frame through the mounting holes located in the Rocker Guard bracket. Then place Guard aside. Center punch the frame where you marked and drill a 5/16" hole in the frame.

**CAUTION:** Before drilling be sure to check the backside of the frame for possible hazards or obstructions.

4. Position Rocker Guard back to the frame and line up holes in the mounting brackets with just drilled holes in the frame. Secure the Rocker Guard to the frame with the included 3/8" x 1" self tapping bolts. Fully tighten all hardware to 10-15 ft/lb. Be sure to use all hardware supplied and tighten all bolts.

5. Repeat steps two through four for the opposite side.