



## INSTALLATION INSTRUCTIONS

MAKE: Nissan  
MODEL: 350Z  
YEAR: 2003-2006  
ENGINE: V6-3.5L  
Also Fits: 2003-2006 Infiniti G35 V6-3.5L

**Twisted Steel Y-Pipe**  
**48-36104-YC (w/Cats)**  
**48-36104-YN (w/o Cats)**



48-36104-YC shown

### Hardware Included

- (P/N 03-50401) Bolt, 10mm (x8)
  - (P/N 03-50400) Nut, 10M (x6)
  - (P/N 05-41061) 2.5" Clamp, Band (x2)
  - (P/N: 05-45953) Y-Pipe Merge (x1)
- 48-36104-YN:
- (P/N: 05-45952) Left Converter Pipe w/o cat (x1)
  - (P/N: 05-45954) Right Converter Pipe w/o cat (x1)
- 48-36104-YC:
- (P/N: 05-45949) Left Converter Pipe w/cat (x1)
  - (P/N: 05-45951) Right Converter Pipe w/cat (x1)

**CAUTION:** Allow time for your vehicle to cool down prior to installation. When working on or under your vehicle proceed with caution. Exhaust systems reach high temperatures and may cause serious burns. Wear protective safety equipment; eye goggles and gloves to ensure a safe installation. aFe recommends professional installation on our products.

- Step 1:** Secure vehicle on jack (refer to your manual for specified jack stand positions).
- Step 2:** Disconnect the Battery.
- Step 3:** Disconnect harness from the Y-Pipe connector and remove the (x2) heated oxygen sensors on both banks. Put marks to identify installation position of each heated oxygen sensors.
- Step 4:** Remove (x2) nuts securing the Y-Pipe to the OE exhaust.
- Step 5:** Remove (x3) nuts securing on the Y-Pipe to exhaust manifold from each side.
- Step 6:** Remove exhaust mounting bracket between Y-Pipe.
- Step 7:** Remove the OE Y-Pipe.
- Step 8:** Assemble aFe Y-pipe on floor or worktable using the 2-1/2" band clamps provided, for easier installation. Do not tighten band clamps.
- Step 9:** Install aFe Y-PIPE using OE gaskets and hardware.
- Step 10:** Re-Install the o2 sensor & each side on the aFe Y-PIPE.
- Step 11:** Re-Install the exhaust mounting bracket.
- Step 12:** Check all your work to make sure everything is tightened.
- Step 13:** Reconnect the battery.
- Step 14:** Installation is now complete. It is recommend to re-tighten all clamps & bolts/nuts after 50-100 miles.



### RACE ONLY DISCLAIMER

This is a Race Only product that is to be used solely for competition, it cannot be used on vehicles that are operated on public streets, roads or highways. Its use is limited to closed-course and open-course racing that is formally sanctioned by a recognized racing organization. Any other use, including recreational off-road use, could be in violation of local, state and federal laws. A competition acknowledgement / liability release form must be filled out and submitted.