



Mounting Instructions for KC #367 C30 LED Bar & Hood Mount Bracket Set for on Jeep JK

Thanks for choosing a KC HiLiTES product. We take pride in building the highest quality, best engineered systems possible. Your satisfaction with our product is important, so if you have any questions, please call our customer service line at 800-528-0950. **For warranty information, visit our website at www.kchilites.com.**

NOTE - This bracket set is designed for the KC 336 30" LED bar only.

Parts Included

- 1 - 30" LED light bar with wiring (KC 336)
- 1 - Hood mount bracket set
- 4 - M8 x 1.25 x 30mm black bolts
- 4 - M8 black washers
- 4 - Spacers

MOUNTING THE BRACKETS

1. Remove the four bolts from the hood hinges that attach the hood.
2. Set one spacer over each hole in the hood hinges.
3. Attach each LED bracket to the hood hinge using the supplied M8 hardware. ***Note - The brackets will be positioned with the slotted hole facing forward and the triangular shape to the outside of the bolts. There should be approximately 31.5" between the bracket mounting slots.*** Start and hand tighten each of the bolts through the LED bracket, spacer, hood hinge and then into the hood. Tighten after all bolts are in place.
4. Install your KC 336 30" LED bar using the hardware and wiring instructions supplied with the LED bar.

YOU'RE DONE