



Rocker Guard

Part No. J004T

Fits: Jeep Wrangler TJ Unlimited (LJ) 2004-2006

Qty	Part Description	Qty	Part Description
16	ST9.5*25 Self Tapping Bolts		

TOLL FREE SUPPORT: 866 638 4870

Install Time : 60 – 180 Minutes
(Professional Installation)
 Install Note : Drilling Requested

REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT

READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION

Rocker Guard Shown



Drilling and Mounting Location

INSTRUCTIONS:

1. Position the guard up to the frame. Maintain a ½" minimum gap between the bottom of the vehicle and the top of the guard. Adjust the Trailblazer Rocker Guard from front to back until it is parallel to the side of the frame while also making sure it is parallel with the side of the vehicle. (Assistance is recommended while installing these guards)
2. When you are satisfied with the placement of the Trailblazer Rocker Guard, mark the side of the frame through the mounting holes located on the Trailblazer Rocket Guard brackets. After you have marked all the holes place the guard to the side. Center punch the frame at the marked locations and drill a 5/16" hole in the frame. Caution: Before drilling be sure to check the backside for hazards or obstructions.
3. Position the Trailblazer Rocker Guard back against the frame and line up the holes in the brackets with the holes that you just drilled on the frame. Secure the Trailblazer Rocker Guard to the frame using the supplied self tapping bolts. Tighten all bolts at this time to 10-15 ft/lb (Figure 1).
4. Repeat these steps to install the other side. Installation is now complete.

Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Sidebar.

For gloss black finishes: Mild soap may be used to clean the Product.

Keystone Automotive Operations Inc. (KAO) warrants this product to be free of defects in material and workmanship at the time of purchase by the original retail consumer. KAO disclaims any other warranties, express or implied, including the warranty of fitness for a particular purpose or an intended use. If the product is found to be defective, KAO may replace or repair the product at our option, when the product is returned prepaid, with proof of purchase. Alteration to, improper installation, or misuse of this product voids the warranty. KAO's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for any incidental or consequential loss or damage.