



Mounting Suggestions Harley-Davidson® FX/FL Big Twin 1958-1984 One-Piece Seat

Tools Required:
Phillips Screwdriver

Hardware:
Stock Rear Fender Screw



Baseplate Features:

The baseplate is 16 gauge steel and features a black powder coat and carpet. Rubber bumpers prevent the baseplate from touching the frame or fender. The chrome rear tab matches stock fender hole.

Stock One-Piece Seat Removal Steps

1. Remove rear fender screw located behind the passenger seat and set aside. The stock rear fender screw will be used to attach your new Mustang One-Piece Seat.
2. Slide seat back and up.

Mounting of Mustang Seat

1. Slide front forks under frame.
2. Align rear tab with stock fender hole.
3. Secure in place with stock fender screw to complete the installation process.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to questions@mustangseats.com, or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers:76379, 75053, 75442, 75619, 75057, 75060, 75630, 75302, 75511, 75734, 75526