



## Mounting Suggestions Harley-Davidson® FLHT/ FLTR Road Glide 1997-2007 One-Piece Seat

Hardware: • Stock Rear Fender Screw



### Baseplate Features:

One-piece touring seats are constructed on extra rugged, triple layered fiberglass. The baseplate is slotted in the middle to allow for use of a driver backrest.

### Removal of Stock One-Piece Seat

1. Remove rear fender screw.
2. Slide seat back and up to remove.

### Mounting of Mustang Solo

1. Engage nose bracket into frame.
2. A firm downward chop to the nose of the seat will push the seat closer to the chrome dash.
3. Push down on rear of seat, align with threaded hole in fender and secure with rear fender screw.

**Enjoy the Comfort of your new Mustang Seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com)

For care and maintenance of our seats, please go to our website under "Support".

Refers to part #'s 75606, 79456, 76587, 76589, 76382, 75454, 75455, 75537, 75570, 75448, 75449