

INSTALLATION INSTRUCTIONS

MAKE: Hyundai
MODEL: Elantra GT Sport
YEAR: 2018
ENGINE: I4-1.6L (t)

**Race-Pipe
Stainless Steel
48-37002-RN**



Professional installation is highly recommended. (Read instructions prior to installation). Make sure to always have at least (2) stands or jacks on hand to support the removal of OE system. Also for the installation of aFe system. Any Removal of rubber isolation mounts may require using a spray lubricant such as WD40 and a pry bar.

Step 1: Read instruction prior to installation. Properly support your stock exhaust system (refer to your owner's manual for specific jack stand positions.) (Note: it is recommended to not fully tighten all band clamps until the entire system has been installed.

Step 2: Remove the TAKEDA Exhaust by unbolting it from the Stock catalytic converter.

Step 3: Remove the Stock catalytic converter.

Step 4: Now install the aFe power race pipe using the gasket and stock nuts.

Step 5: Install the resonator pipe, and the mid pipes as shown into the race pipe using the provided 3" clamps.

Step 6: Install the TAKEDA Cat-back using the gasket, and stock nuts.

Step 7: Adjust system and begin tightening all clamps and hardware starting from the front and working your way to the rear.

Step 8: Congratulations your exhaust is now complete it is recommended to re-tighten all clamps and hardware 50-100 miles after installation.



Caution: Allow time for your vehicle to cool down prior to installation. When working on or under your vehicle proceed with caution. Exhaust systems reach high temperatures and may cause serious burns. Wear protective safety equipment; eye goggles and gloves to ensure a safe installation. **aFe recommends professional installation on our products.**