




INSTALLATION INSTRUCTIONS

**Metal Mulisha Stainless Steel Exhaust
2011-12 Ford F-150 Truck 3.5L Eco Boost
Super Crew - Short Bed 5.5"
PART #60-0018**



ITEM	PART #	QTY	DESCRIPTION
A	1404-701149S	1	3.0" Headpipe with Flange
B	MM023	1	Muffler Assembly
C	MM018	1	4.0" Overaxle pipe
D	61-1036	1	6" Metal Mulisha Exhaust Tip
E	OHD300	1	3.0" Clamp
F	5759	1	4.0" Band Clamp
G	BO-1020	1	Bolt Kit for Headpipe

Note: This exhaust will exceed some state sound laws and requirements. Aggressive driving will get you noticed and can result in a ticket or warning from your local law enforcement agency.

EXHAUST INSTALLATION

PART# 60-0018

WHEN INSTALLING THIS EXHAUST SYSTEM MAKE SURE TO USE ALL THE PROPER SAFETY PRECAUTIONS. USE JACK STANDS WHEN UNDER TRUCK, SET PARKING BRAKE, BLOCK TIRES AND USE SAFETY GLASSES.

DO NOT WORK WITH HOT PIPES!!!

1. Disconnect the negative battery cable before removal of the OEM Exhaust. This will allow the computer to reset and recognize the new exhaust. Lay out the exhaust on the floor so it looks like the drawing and compare parts with manual. Remove the factory exhaust by cutting behind the factory muffler. Once the tail pipe has been removed un-bolt the muffler and head pipe at the flange located in front of the factory muffler. Use wd-40 or another type of penetrating oil to remove the rubber grommets. Do not damage these they will be re used.



2. Install Head pipe Item # A onto the factory two bolt flange. Use Bolt kit Item #G to secure the flange connection. Install hanger into rubber grommet and loosely tighten down the flange.



3. With the head pipe and hangers in position install the muffler assembly Item # B. You will use the Clamp Item # E to secure to the head pipe. Do not tighten keep loose.



4. Use a jack stand to support the muffler assembly until you have installed the over axle pipe Item # C



5. Install the over axle pipe. With everything loose you may need to adjust the system for proper clearance of shocks, brake lines, ect.



6. With proper clearance from spare tire install the exhaust tip onto the tailpipe. The system was designed to have the tip 1" below the quarter panel of the vehicle. With the tip in your desired position begin to tighten down all clamp connections from the front head pipe back.



7. Be sure to check all clearance after each section has been tightened to be sure there is proper clearance. It may take 4-500 miles for your vehicle to fully adjust to the changes in exhaust flow.