\$5074 09-12 CHEV COLORADO/GMC CANYON, 5.3L, EXTENDED/CREW CAB-SHORT BOX, CAT BACK,	
	10 12 13 13 AIL A
 EXTENSION PIPE MUFFLER PASSENGER SIDE OVER AXLE PIPE DRIVER SIDE OVER AXLE PIPE CROSS PIPE PASSENGER SIDE TAIL PIPE DRIVER SIDE TAIL PIPE 2 1/2" CLAMP(5PCS) 5/16" X 1" BOLT (2PCS) 5/16" NUT (2PCS) 5/16" NUT (2PCS) 5/16" WASHER (2PCS) 5/16" WASHER 2 3/4" CLAMP 3" CLAMP EXHAUST TIP (2PCS) NOTE: SADDLE CLAMPS USED IN ALUMINIZED SYSTEMS NOTE: SPARE TIRE REMOVAL IS REQUIRED FOR THIS SYSTEM 	
PLEASE READ BEFORE STARTING INSTALLATION While MBRP Inc. has made every effort to ensure that all components of the are of superior quality and properly packaged, it is the installer's respons ensure the following before removal of the factory exhaust:	is system ibility to
 that ALL components shown above are present. that ALL mating components fit together. that there are no damaged components. that the system you have purchased is appropriate for your vehicle year, configuration. that the system will not interfere with any modifications previously installed that you have read and understand these instructions. 	
If you have any questions or are uncertain about any aspect of the installation system to your vehicle please contact your dealer before commencing ins	ion of this tallation. GE 1 OF 4





Figure 1



Figure 2



Figure 3



Figure 4

Note: This System requires spare tire removal

Removal of Stock System:

1. Apply a penetrating lubricant liberally to all exhaust fasteners, hangers and rubber insulators.

2. Cut the exhaust in rear of the muffler so that the tail section can be removed from the vehicle.

3. Measure 4 1/2" in front of the cross member. The cross member is located just behind the Y-pipe. **Refer to Figure 2**.

4. Remove the hangers from the rubber insulators. Remove the exhaust from the vehicle. **Refer to Figure 3**.

5. Remove spare tire from the vehicle and relocate.

Installation of MBRP Inc. Performance Exhaust:

Install the **Extension Pipe** to the end of the Y-pipe using the $2\frac{3}{4}$ " amp. Refer to Figure 4.



Figure 5



Figure 6



Figure 7



Figure 8



Figure 9

MBRP

2. Slide a 2 ½" Clamp over the Extension Pipe and install the Muffler Assembly onto the Extension Pipe. Using another 2 ½" Clamp slide the Passenger Side Over Axle Pipe into the driver side of the Muffler Assembly. Attach the two hangers into to the existing rubber insulator at the front and back of the Muffler Assembly. Refer to Figure 5. Note: Driver side of Muffler Assembly leads to Passenger Side Tailpipe and vice versa.

3. Slide a 2 ½" Clamps over the outlet of the Passenger Side Over Axle Pipe. Position the Passenger Side Tail Pipe and loosely attach it to the Passenger Side Over Axle Pipe. Install the Passenger Side Tail Pipe hanger into the existing rubber insulator. Refer to Figure 6.

4. Loosely install the **Driver Side Over Axle Pipe** to the passenger side of the **Muffler**. **Refer to Figure 7**.

5. Slide a 2 ¹/₂" Clamp over the Driver Side Over Axle Pipe then loosely attach the Cross Pipe to the Driver Side Over Axle Pipe. Refer to Figure 8.

6. Install the **Hanger Assembly** using the fasteners provided. Note some vehicles may require drilling to enlarge the one hole. **Refer to Figure 9**.

MBRP



Figure 10



Figure 11

7. Slide a 2 ¹/₂" Clamp onto the Cross Pipe and then attach the Driver Side Tail Pipe hanger into the Hanger Assembly and to the Cross Pipe. Refer to Figure 10.

8. Install and adjust the **Exhaust Tips** to suit. Tighten the lock bolt located on each **Exhaust Tip**. **Refer to Figure 11**.

9. Align the exhaust as required. Starting at the front of the exhaust, tighten all clamps and connections.

10. Check along the whole length of the exhaust system to ensure that there is adequate clearance around the spare tire, fuel and brake lines or any wiring. If any interference is detected relocate or adjust.



Congratulations! You are ready to begin experiencing the improved power, sound and driving experience of your MBRP Inc. performance exhaust system. We know you will enjoy your purchase.